

20028 San Vittore Olona (Milan - Italia) - Via G. Puccini, 14 - Tel. +39 0331.422150 r.a.– Fax +39 0331.422160 – P.IVA e CCIAA IT 07022110964 – REA 1929995 - <u>www.eurografica.mi.it</u> - <u>info@eurografica.mi.it</u>

DATA SHEET LEADER MACHINE

Plate Washing Machine Mod "LEADER SPEED" - MARK CE

Plate Washing Machine Mod "LEADER S SPEED" - MARK CE <u>HEAVY DUTY MACHINE – DOUBLE SPEED</u>

- Max plate width: **cm. 88** 118 138
- Automatic start of all work-phases is completely controlled by dedicated Micro-Computer.
- Rollers straightening any input folds of pliers.
- **Double automatic wash cycles** with dual rotating brushes in each of the two different sections, two separated stainless steel tanks with independent motors and independent stainless steel tanks for the cleaners-solvents storage. With this system is possible to produce a big number of Offset plates per days: 70 meter per hour.
- Automatic rinsing cycle with one rotating brush with independent motors and warm water. This is a very important cycle.
- Adjustable cycle-speed (rollers speed).
- Gumming section and drying on both sides of the plate with hot air (adjustable power).
- All parts in contact with cleaner-solvent, gum and warm water are in stainless steel.
- Tanks service entered in a drawer with sliding movement of the liquid is completely closed loop.
- Semi-automatic washing cycle of gumming rollers, with micron-switch for safety position control of the lever faucet.
- Warm water recycle unit with electrical resistance.
- Dedicated Micro-Computer control with the presence of water recycling, water temperature (factory set at + / - 35 ° C), plate washed count (can reset), automatic control power of the heating elements of hot air dryer, warning on the display of errors and the stages of work of the machine.
- Notice by led light green and display of the dedicated Micro-Computer for free admission for the insertion of plates in sequence.
- Tanks capacity service: 2 tanks Lt.40 cleaner-solvent, 1 tank Lt. 10 for the gum and 1 tank Lt. 10 for the water of gumming rollers washing cycle.
- Warm water external recycle unit capacity Lt.80.



